





Comparison Table of GV-VMS and GV-DVR / NVR

		GV-VMS	GV-DVR / NVR
Software Interface			
General Information			
Live View UI		Fixed windows	
Theme Color		Light / black style	Silver (metal) style
Supported Languages		22 languages	31 languages
Supported OS	32-bit	Not supported	Windows 7 / 8 / 8.1 / 10 / Server 2008
	64-bit	Win 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 R2 / Server 2016	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 R2
Note: GV-VMS V18.1 or later is only supported by Windows 10 / Server 2016 or later.			
Supported Database (Event Log)		Microsoft Office Access, Microsoft SQL	Microsoft Office Access
Webcam Server Support		O	
Supported Devices		<ul style="list-style-type: none"> • GV-IP Devices • 3rd party IP cameras (26 brands) • ONVIF, PSIA, RTSP protocols 	
Video Capture Cards		Not supported	O (Supports analog cameras)
Free License		32 ch of GV-IP Devices	
Maximum License	GV-IP Devices	GV-VMS Pro: Up to 64 ch GV-VMS: Up to 32 ch	Up to 32 ch
	3rd party IP Cameras	1 to 64 ch in increments of 1 ch	1 to 32 ch in increments of 2 ch
Trial License	3rd party IP Cameras	16 channels	Not supported
Note: GV-VMS V18.1 or later is a paid software and does not offer any free or trial licenses.			
Monitoring			
Multi-Screen Support		O (Through layout)	O (Through Digital Matrix)
Layout		<ul style="list-style-type: none"> • Default: 8, 10, 13, 17, 33 ch • 1 x 1 ~ 10 x 10 live view grids <ul style="list-style-type: none"> • Customizable layout • GV-Decoder Box for remote monitor display⁽³⁾ 	1, 4, 6, 8, 9, 10, 12, 16, 25, 32 ch



Layout Scan Function	O	Not supported	
Duplicating Layout	O	Not supported	
Drag and Drop Support	O	Not supported	
GPU Decoding	Intel GPU	O	
	External NVIDIA graphics cards	Not supported	
H.265 GPU decoding	O	O	
H.265 Codec	O	O	
On-Demand (Dual Stream)	O	O	
Service Mode	O	Not supported	
Supported Screen Resolutions	1024 x 768 or above (Supports 4k / 2k resolution)	800 x 600, 1024 x 768, 1280 x 1024, 1680 x 1050, 1600 x 1200, 1920 x 1080, 1280 x 800, 1920 x 1080, 1440 x 900	
Motion Detection	O (Sensitivity: 1~10)		
Video Analytics	Object Index, Privacy Mask, Defog, Stabilizer, Intruder, Counter, Crowd Detection, Advanced Unattended Object, Advanced Scene Change, Advanced Missing Object, Face Count, Face Detection, Face Search, Text Overlay Face Recognition ⁽³⁾ , Face Detection by Camera ⁽³⁾ , Face Search ⁽³⁾ , 3D People Counting and Heat Map are only supported by GV-VMS		
Image Orientation For Corridor Scenes	O	Not supported	
Connection Lost / Video Lost Detection	O		
Storyline	O	Not supported	
E-Map	O (Camera View, I/O Alarm)		
System Log	O		
Account Management	Up to 1,000 accounts (Supervisor / Power User / User / Guest)		
I/O Device Control	O		
Notification	E-Mail Alert	O	
	I/O Alarm	O	
	Computer Alarm	O	
	SMS Alert	Not supported	O
	SNMP Protocol	O	Not supported
PTZ Control	O (PTZ control panel, keyboard / joystick)		
Fisheye Support	O (fisheye dewarping, auto pan, preset functions, object tracking)		
Smart Streaming	O	Not supported	



Dual Streaming of GV-Fisheye Camera		O	Not supported
Two-Way Audio		O	
System Idle Protection		O	
POS Solution		O	
Recording and Playback			
Recording	Function	O (post/pre-recording, digital watermark)	
	Video Clip	1 – 5 min	
	Storage Group	24 groups	16 groups
Video Playback	Max. Channels	64	16
	Video Timeline	O	Not supported
	Audio Timeline	O	Not supported
	Mark/Unmark recycle	O	
Displaying Object Search Results in a Timeline		O	Not supported
Bookmarking	Live View	O	Not supported
	Playback	O	Not supported
Instant Playback		O (10 sec / 30 sec / 1 min / 5 min)	
Recording Schedule		O	
Merge Clips & Save as AVI	Full frame	O	
	Key frame	O	Not supported
Daylight Saving Time (DST)		O	
Remote ViewLog		O	
Event Backup		O	
Remote Monitoring Software			
Web Browsers		O (IE / Safari / Firefox / Chrome)	
GV-Eye for Android / iOS		O	
GV-Eye Connection by QR Code		O ⁽³⁾	Not supported
GV-Control Center		O	
GV-CMS		O	
GV-Failover / Redundant Server		O ⁽¹⁾	O
GV-Backup Center		O	
GV-Mobile Server		O	
GV-Edge Recording Manager	Windows	O	
	Mac	O	Not supported



	Software & Utility	
GV-Web Report	<input type="radio"/> ⁽²⁾	<input type="radio"/>
GV-ASManager with LPR Plugin	<input type="radio"/> ⁽²⁾	<input type="radio"/>
GV-Authentication Server		<input type="radio"/>
GV-Bandwidth Control		<input type="radio"/>
GV-Backup Viewer	Not supported	<input type="radio"/>
GV-Dynamic DNS V2		<input type="radio"/>
E-Map Server		<input type="radio"/>
Fast Backup & Restore (FBR)		<input type="radio"/>
GV-IP Device Utility		<input type="radio"/>
GV-Local DDNS	Not supported	<input type="radio"/>
GV-Multi View	Not supported	<input type="radio"/>
GV-Multicast	Not supported	<input type="radio"/>
GV-MultiLang Tool		<input type="radio"/>
GV-SetLanguage		<input type="radio"/>
GV-Mcamctrl Utility		<input type="radio"/>
GV-Remote ViewLog		<input type="radio"/>
GV-Remote E-Map		<input type="radio"/>
GV-SMS Server	Not supported	<input type="radio"/>
GV-SD Card Sync Utility		<input type="radio"/>
GV-Live Streaming	<input type="radio"/> ⁽³⁾	<input type="radio"/>
Media Man Tool		<input type="radio"/>
Report Generator	<input type="radio"/> ⁽³⁾	<input type="radio"/>

Note:

1. GV-VMS is only supported by GV-Failover / Redundant Server V1.1.0.0 or later.
2. GV-VMS is only supported by GV-Web Report V2.2.6.0 and GV-ASManager with LPR Plugin V4.3.5.0 or later.
3. These features / functions are only available on GV-VMS V18.1 or later, a paid version of GV-VMS.
4. All specifications are subject to change without notice.